

## VIGILANT S800

Scalable Storage for  
Complex Surveillance  
Environments



The Vigilant S800 is a high-performance 2U rackmount solution designed to simplify large-scale surveillance deployments at a competitive price. Engineered for seamless integration and reliable operation in complex applications, the S800's efficient architecture scales effortlessly to meet evolving security needs. Partner with Now Micro to reduce risk, save time, increase profits and maximize efficiency with purpose-built solutions that are backed by people who care and powered by innovation.

### KEY FEATURES



Intel® Quick Sync for enhanced video processing speed



Up to 192TB of raw storage for large-scale systems



Flexible RAID options for worry-free data redundancy



8-bay 2U rackmount form factor for efficient installation



Integrated DICE software for streamlined system monitoring



Every Now Micro solution comes equipped with DICE technology, offering OEMs and systems integrators a powerful suite of tools that streamlines deployment, reduces downtime with remote monitoring and simplifies asset management through a single, intuitive portal.



DICE MANAGE



DICE INTEGRATE/  
ENGAGE



DICE BACKUP



DICE SUPPORT



DICE DEPLOY



DICE REMOTE



DICE HEALTH



DICE ASSET



# VIGILANT S800

## System

### PROCESSOR

- Intel® Core™ i5/i7/i9

### OPERATING SYSTEM

- Windows 11 IoT Enterprise LTSC
- Windows 10 IoT Enterprise LTSC
- Windows 11 Professional
- Linux

### MEMORY

- 16GB Standard, Supports Up to 128GB
- 4 x DDR4 DIMM slots

### CAPACITY

- Up to 192TB

### RAID

- Hardware RAID, JBOD, 0, 1, 5, 6, 10

### STORAGE CONTROLLERS

- Intel® Q670 Chipset

### GRAPHICS

- Intel® UHD Graphics 730 (Core™ i5)
- Intel® UHD Graphics 770 (Core™ i7, i9)

### GRAPHIC CARD OPTIONS

- NVIDIA RTX A400, 4GB, 4 x mDP
- NVIDIA RTX A1000, 8GB, 4 x mDP

### I/O PORTS

#### Front:

- 2 x USB 3.0

#### Rear:

- 2 x USB 3.2 Gen 1 ports
- 3 x USB 3.2 Gen 2 ports
- 1 x USB 3.2 Gen 2 port (Type C)
- 4 x DisplayPort
- 3 x 3.5mm Audio, Line Out, Line In, Mic In
- 1 x Serial (RS232/422/485)

### NETWORKING

- 2 x 2.5GbE RJ-45
- 1 x 1GbE RJ-45

### EXPANSION SLOTS

- 2 x PCIe x16 Half Height (1 x16, 2 x8, Open)
- 2 x PCIe x4 Half Height (Open)

### NIC OPTIONS

- 4 x 1GbE RJ-45
- 2 x 10GbE RJ-45
- 2 x 25GbE SFP28

### SECURITY MODULE

- Intel® Platform Trust Technology

### HARDWARE MONITORING

- Now Micro DICE Enhancements Pre-Installed

### WARRANTY

- 3-Year On-Site Warranty
- Optional 5-Year On-Site Warranty

## Mechanical

### FORM FACTOR

- 2U Rackmount

### OS DRIVES

- 1 x 250GB M.2 SSD

### DATA DRIVES

- Up to 8 x 3.5in Surveillance Class SATA Swappable Drives

### POWER SUPPLY

- Single Power Supply, 500w
- Optional Redundant Power Supply, 550w

### OPERATING TEMPERATURE

- 50°F to 95°F (10°C to 35°C)

### OPERATING HUMIDITY

- Up to 80%, Non-Condensing

### DIMENSIONS

- Height – 3.42in (87mm)
- Width – 17.24in (438mm)
- Depth – 21.94in (557.2mm) Not Including Bezel